

**The Dell™ PowerEdge™ R710 is designed to be the cornerstone of today's competitive enterprise. Engineered in response to input from IT professionals, it is the next-generation 2U rack server created to efficiently address a wide range of key business applications. The successor to the PowerEdge 2950 III, the R710 runs the Intel® Xeon® 5500 and 5600 Series Processors and helps you lower the total cost of ownership with enhanced virtualization capabilities, improved energy efficiency, and innovative system management tools.**

#### **STRONG IT FOUNDATION**

As an IT professional, you want a data center built to allow for organic growth and the ability to scale based on your company's changing requirements. You need complete solutions that allow you to focus your time and money on managing and growing your business. Dell understands your needs and responds with an expanding portfolio of enterprise servers, storage technologies, and services with a single goal: to help you simplify IT.

#### **PURPOSEFUL DESIGN**

The R710 takes advantage of Dell's system commonality. Once your IT managers learn one system, they understand how to manage next-generation Dell servers. Logical component layout and power supply placement also provide a straightforward installation and redeployment experience.

Featuring 18 DIMM slots and 4 integrated network connections, the R710 delivers the critical components to virtualization and database performance. The Intel Xeon processor series 5500 and 5600 adapt to your software in real time, processing more tasks simultaneously. Using Intel® Turbo Boost Technology, the R710 can increase performance during peak usage periods. You can then help reduce operating costs and energy usage with Intel® Intelligent Power Technology, which proactively puts your server into lower power states when demand decreases. Increased memory slots also save money by enabling you to use smaller, less-expensive DIMMs to meet your computing needs.

In addition, Dell's latest PowerEdge servers provide a graphical and interactive LCD for system health monitoring, alerting and control of basic management configuration right in the front of the server. Customers have an AC power meter and ambient temperature thermometer built into the server which they can monitor on this display without any software tools.

#### **ENHANCED VIRTUALIZATION**

Featuring Intel Xeon-based architecture, embedded hypervisors, large memory capacity, and integrated I/O, the next-generation Dell PowerEdge R710 delivers better overall system performance and greater virtual machine-per-server capacity. With optional factory-integrated virtualization capabilities, you get tailored solutions—built with the latest technologies from Dell and our trusted partners—which allow you to streamline deployment and simplify virtual infrastructures. Choose your hypervisor from market leaders such as VMware®, Citrix®, and Microsoft®, and enable virtualization with a few mouse clicks.

#### **ENERGY-OPTIMIZED TECHNOLOGIES**

Using the latest Energy Smart technologies, the R710 reduces power consumption while increasing performance capacity versus the previous generation servers. Enhancements include efficient power supply units right-sized for system requirements, improved system-level design efficiency, policy-driven power and thermal management, and highly efficient standards-based Energy Smart components.

## SIMPLIFIED SYSTEMS MANAGEMENT

The next generation Dell OpenManage™ suite offers enhanced operations and standards-based commands designed to integrate with existing systems for effective control.

## LIFECYCLE CONTROLLER

Lifecycle Controller is the engine for advanced systems management integrated on the server. Lifecycle Controller simplifies administrator tasks to perform a complete set of provisioning functions such as system deployment, system updates, hardware configuration and diagnostics from a single intuitive interface called Unified Server Configurator (USC) in a pre-OS environment. This eliminates the need to use and maintain multiple pieces of disparate CD/DVD media.

## DELL MANAGEMENT CONSOLE (DMC)

The new Dell Management Console, powered by Altiris™ from Symantec™, delivers a single view and a common data source into the entire infrastructure. Dell Management Console is built on the Symantec Management Platform (formerly Altiris Notification Server), an easily extensible, modular foundation that can provide basic hardware management or more advanced functions such as asset and security management. Dell Management Console helps reduce or eliminate manual processes so less time and money is spent keeping the lights on and more time can be spent on strategic uses of technology.

## DELL GLOBAL SERVICES

Dell Services can help reduce IT complexity, lower costs, and eliminate inefficiencies by making IT and business solutions work harder for you. The Dell Services team takes a holistic view of your needs and designs solutions for your environment and business objectives while leveraging proven delivery methods, local talent, and in-depth domain knowledge for the lowest TCO.

FEATURES		R710
<b>Form Factor</b>	2U rack height	
<b>Processors</b>	Latest quad-core or six-Core Intel® Xeon® 5500 and 5600 series processors	
<b>Processor Sockets</b>	2	
<b>Interconnect</b>	Intel® QuickPath Interconnect (QPI)	
<b>L2/L3 Cache</b>	4MB and 8MB	
<b>Chipset</b>	Intel® 5520	
<b>Memory</b>	Up to 144GB (18 DIMM slots*): 1GB/2GB/4GB/8GB DDR3, 800MHz, 1066MHz or 1333MHz	
<b>I/O Slots</b>	2 PCIe x8 + 2 PCIe x4 G2 Or 1 x16 + 2 x4 G2	
<b>Drive Controller</b>	PERC6/i or SAS6/iR, PERC 5/E and PERC 6/E	
<b>RAID Controller</b>	<b>Internal:</b> PERC H200 (6Gb/s) PERC H700 (6Gb/s) with 512MB Non-Volatile cache PERC H700 (6Gb/s) with 512MB battery-backed cache SAS 6/iR PERC 6/i with 256MB battery-backed cache PERC S100 (software based) PERC S300 (software based)	<b>External:</b> PERC H800 (6Gb/s) with 512MB Non-Volatile cache PERC H800 (6Gb/s) with 512MB of battery-backed cache PERC 6/E with 256MB or 512MB of battery-backed cache <b>External HBAs (non-RAID):</b> 6Gbps SAS HBA SAS 5/E HBA LSI2032 PCIe SCSI HBA
<b>Drive Bays</b>	8 x 2.5" Hard Drive Option or 6 x 3.5" Hard Drive Option; Optional flex bay expansion to support half-height TBU Up to four 3.5" drives with optional flex bay OR Up to eight 2.5" SAS or SATA drives with optional flex bay	
<b>Maximum Internal Storage</b>	6TB SATA or Near Line SAS	
<b>Hard Drives<sup>1</sup></b>	2.5" SAS (10K RPM): 36GB, 73GB, 146GB, 147GB, 300GB 2.5" SAS (15K RPM) 36GB, 73GB 2.5" SATA II (5.4K RPM): 80GB, 160GB, 250GB 2.5" SATA II (7.2K RPM): 80GB, 120GB, 160GB, 250GB 2.5" 500GB SATA	3.5" SATA (7.2K): 80 GB, 160GB, 250GB, 500GB, 750GB, 1TB 3.5" SAS (10K): 400GB 3.5" SAS (15K): 73GB, 146GB, 300GB, 450GB 3.5" Near-Line SAS (7.2K): 500GB, 750GB, 1TB 3.5" 2.0TB SATA
<b>Network Interface Cards</b>	Four embedded Broadcom® NetXtreme II™ 5709c Gigabit Ethernet NIC with failover and load balancing; TOE (TCPIP Load Engine) supported on Microsoft® Windows Server® 2003 SP1 or higher with Scalable Networking Pack; Optional 1GbE and 10GbE add-in NICs Broadcom® NetXtreme II® 57711 Dual Port Direct Attach 10Gb Ethernet PCI-Express Network Interface Card with TOE and iSCSI Load Intel® Gigabit ET Dual Port Server Adapter and Intel® Gigabit ET Quad Port Server Adapter Dual Port 10Gb Enhanced Intel Ethernet Server Adapter X520-DA2 (FcoE Ready for Future Enablement)	
<b>Power Supply</b>	Energy Smart – Two hot-plug high-efficient 570W PSU OR High Output Two hot-plug 870W PSUs	
<b>Uninterruptible Power Supplies</b>	1000W-5600W 2700W-5600W High Efficiency Online Extended Battery Module (EBM) Network Management Card	
<b>Availability</b>	DDR3: hot-plug hard drives; optional hot-plug redundant power supplies; dual embedded NICs with failover and load balancing support; PERC 6/i: optional PERC5/i integrated daughtercard controller with battery-backed cache; hot-plug redundant cooling; tool-less chassis; fibre and SAS cluster support; validated for Dell/EMC SAN	
<b>Video</b>	Matrox G200 with 8MB of cache	
<b>Remote Management</b>	iDRAC6	
<b>Systems Management</b>	Dell™ OpenManage™	
<b>Rack Support</b>	4-post (Dell rack), 3rd party Versa rails, sliding rails and Cable Management Arm	
<b>Fans</b>	Standard redundant cooling	
<b>Acoustics</b>	Typically configured** 2.5" chassis in 23 +/- 2 C ambient Idle: LwA-UL*** = 5.5 bels, LpAm**** = 39 dBA	
<b>Operating Systems</b>	Microsoft® Windows® Small Business Server 2008 Microsoft® Windows® Essential Business Server 2008 Microsoft® Windows Server® 2008 SP2, x86/x64 (x64 includes Hyper-V™) Microsoft® Windows Server® 2008 R2, x64 (includes Hyper-V™ v2) Microsoft® Windows® HPC Server 2008 Novell® SUSE® Linux® Enterprise Server Red Hat® Enterprise Linux® Sun® Solaris™	
<b>(Optional) Embedded Hypervisors</b>	For more information on the specific versions and additions, visit <a href="http://www.dell.com/OSsupport">www.dell.com/OSsupport</a> . Citrix® XenServer™ VMware® ESXi v3.5	

1 For hard drives, GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.

\*\* 'Typical configuration' means the system is populated with projected average quantity, type, capacity, speed, etc., of components

\*\*\* LwA – UL is the upper limit sound power levels (LwA) calculated per section 4.4.1 of ISO 9296 (1988) and measured in accordance to ISO

7779 (1999)

\*\*\*\* LpAm is the average bystander position A-Weighted sound pressure level calculated per section 4.4.4 of ISO 9296 (1988) and measured

in accordance to ISO 7779 (1999)

## SIMPLIFY YOUR SERVERS AT [DELL.COM/PowerEdge](http://DELL.COM/PowerEdge)

Copyright Dell 2010. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, and OpenManage are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind.

